




Mounting: recessed into ceiling	LED: COB (Citizen)	LED driver: remote	Areas of use:
Housing: aluminum alloy	CRI: Ra> 92/85	Volt AC: 220-240V	indoors:
Duffuser: polycarbonate	CCT:	LED driver options:	public/ private/ residential
Finish options:	CT27-2700k	ND - non-dimmable	
01-white matte	CT30-3000k	PH - phase dimmable	
11-black matte	CT40-4000k	010V - 0-10V dimmable	
	CT50-5000k	DALI - compatible	
	CT60-6000k	Note: *Lm given in data is based on 3000k	
			5 years warranty RoHS F III CE IP54



Ref Code	Watt	mA	Lm(±)
03.05.125.01.08	8W	700	683
03.05.125.02.10	10W	700	850

Beam Angle-Code:


- 24°-BA24
- 36°-BA36
- 60°-BA60



Ref Code	Watt	mA	Lm(±)
03.05.126.01.13	13W	350	1170
03.05.126.02.20	20W	350	1800

Beam Angle-Code:

- 24°-BA24
- 36°-BA36
- 60°-BA60



Ref Code	Watt	mA	Lm(±)
03.05.140.01.10	10W	500	850

Beam Angle-Code:

- 24°-BA24
- 36°-BA36
- 60°-BA60

