

Mounting: recessed in wall
Housing: stainless steel 1.4401(SUS316)/
 die-cast aluminum
Trim: stainless steel 1.4401(SUS316)/
 die-cast aluminum
Diffuser: opal tempered glass
Finish options (of aluminum parts):
 01-white matte/11-black matte
 13-grey matte


LED: SMD
CRI: Ra>80 (±3000K)
CCT:
 CT30-3000K
 CT40-4000K
 CT60-6000K
Note:
 * RGB/RGBA is available on request
Nominal efficacy: 100 lm/W

LED driver options:
 integral/ remote
Volt AC: 240V
Volt DC: 24V
Frequency: 50-60Hz
LED driver options:
 ND - non-dimmable
 PH - phase dimmable
 010V - 0-10V dimmable
 DALI - compatible


Application:
 outdoors:
 in vertical positions
 stairs, walls, corridors, steps
Ambient Temp: -30°~+50°C




housing: stainless steel 1.4401(SUS316)
 trim: stainless steel 1.4401(SUS316)




Ref Code	Watt	Lm(±)	Volt	DiaxL1xL2
27.45.029.01.1.5	1.5W	125	24V DC	36x100x60
27.45.030.01.1.5	1.5W	125	24V DC	56x105x70
27.45.031.01.2.5	2.5W	166	24V DC	80x105x70



housing: die-cast aluminum
 trim: stainless steel 1.4401(SUS316)




Ref Code	Watt	Lm(±)	Volt
27.45.032.01.03	3W	210	24V DC




Beam angle: 90°


housing: die-cast aluminum
 trim: stainless steel 1.4401(SUS316)



Ref Code	Watt	Volt	L1xL2xH1xH2xW
27.45.033.01.03	3W	24V DC	115x106x72x46x50
27.45.034.01.04	4W	24V DC	170x160x73x47x65
27.45.035.01.06	6W	24V DC	260x256x110x81x76



housing: die-cast aluminum
 trim: die-cast aluminum



Ref Code	Watt	Volt	L
27.45.036.01.5.5	5.5W	240V AC	185
27.45.037.01.6.5	6.5W	240V AC	230
27.45.038.01.7.5	7.5W	240V AC	260
27.45.039.01.10	10W	240V AC	320

